



Technical data sheet  
**LACQUER FOR BOATS**

for the protection and  
decoration of wood

**Basic composition:**

Colorless coating based on alkyd binder, additives and organic solvents.

**Purpose:**

Decorative wood protection is used in the exterior and interior. Effectively protects wood in all climatic conditions. It is used to protect boats, construction carpentry, garden furniture, paneling.

**Properties:**

Boat varnish is characterized by high gloss, water and weather resistance. It is easily applied with a brush and penetrates well into the pores of the wood. It can be used on its own or over a lacquer coating when a high gloss finish effect is desired.

**Method of application:**

Pre-cleaned and sanded wood is applied with a brush or by spraying. It is thinned with an oil thinner to a viscosity suitable for spraying. Brush work does not require thinning. It is applied in two to three layers. It dries completely in 24 hours, at a relative air humidity of 65% and a temperature of 20 °C. Wash accessories with oil thinner.

**Technical data:**

Delivery viscosity (F/4, 20°C): 110±10 s  
Content of non-volatile substances: 44 ±2 %  
Specific gravity: (20°C) 0.90± 0.01kg/lit.

Drying time: (at 20°C, 65% humidity)

- on touch: 5-6 h  
- full 24 h

**Consumption:**

1 liter covers 5-6 m<sup>2</sup>.

**Delivery form:**

It is delivered in tin packaging in the following volumes: 0.75 liters, 5 liters and 20 liters.

**Storage:**

3 years in the original packaging, at a temperature of up to 30°C.

**Precautions**

The application of safety measures at work and fire protection is mandatory. Follow the manufacturer's instructions and safety data sheets.

The technical data are given in order to optimally use the product.

For all necessary information, contact the manufacturer