



Technical data sheet  
**NITRO BASIC COATING FOR WOOD**

**Basic composition:**

White coating based on nitrocellulose synthetic binder, special pigments, organic solvents and special auxiliaries that enable good sanding.

**Purpose:**

It is intended for the processing of veneered and solid wood as a base coating in a system with nitro pigmented coatings (matte, semi-matte and high gloss).

**Properties:**

It penetrates deep into the pores of the wood, gives a full film, is characterized by fast drying and sanding. Enables better adhesion of covering coatings. It fills the unevenness of the wood, reduces the roughness of the surface and covers the wood structure well. Dries in 30 minutes at a temperature of 20°C and a relative humidity of 65%.

The coating must not be applied at air humidity higher than 65% because it turns white.

**Method of application:**

It is applied in one or two layers on a clean and sanded wood surface. It can be applied by pneumatic and airless spraying.

It is diluted 20-30% with Nitro Thinner - D.

**Consumption:**

1kg is enough for 6-8m<sup>2</sup>.

Washing tools: Nitro thinner.

**Packaging:**

In tin packaging, 0.9 kg, 6 kg and 25 kg.

**Shelf life:**

3 years at a temperature of up to 25°C.

**Precautions**

The application of safety measures at work and fire protection is mandatory. Follow the manufacturer's instructions and safety data sheets.

The technical data are given in order to optimally use the product.

For all necessary information, contact the manufacturer

Producer : CHIARA d.o.o. Brčko distrikt BiH, Bescarinska zona bb,  
Tel: 049 240 400, fax: 049 240 401, 049 240 415, e:mail : [info@chiara.ba](mailto:info@chiara.ba) , web site: [www.chiara.ba](http://www.chiara.ba)