



Technical data sheet
NITRO SYRINGE PUTTY

Basic composition:

Pigmented coating based on nitrocellulose, synthetic binder, pigments, additives and specially selected fillers.

Purpose:

It is intended for leveling pores and unevenness in wood. It is applied as a base coat in the wood protection system.

Properties:

It is characterized by good adhesion to the wooden surface.

It fills the pores and unevenness of the wood well.

It is characterized by quick drying. It dries in 30 minutes at a temperature of 20°C and air humidity of 65%.

It is easy to sand after 60 minutes from the moment of application.

Method of application:

Before use, the contents of the paint must be mixed well.

It is diluted with Nitro Thinner - D about 20%.

It is applied by pneumatic spraying in one or two layers on a clean and dry wood surface.

It can also be applied over Nitro base paint for wood.

Consumption:

1 kg is enough for 6-7 m².

Washing tools: Nitro thinner.

Packaging:

In tin packaging 1kg and 25kg.

Shelf life:

3 years at a temperature of 25°C.

Precautions

The application of safety measures at work and fire protection is mandatory. Follow the manufacturer's instructions and safety data sheets.

The technical data are given in order to optimally use the product.

For all necessary information, contact the manufacturer

Producer : CHIARA d.o.o. Brčko distrikt BiH, Bescarinska zona bb,

Tel: 049 240 400, fax: 049 240 401, 049 240 415, e:mail : info@chiara.ba , web site: www.chiara.ba