



Technical data sheet
VARNISH
Impregnation for wood

Basic composition:

Transparent coating based on alkyd binder and organic solvents.

Purpose:

It is recommended for the impregnation of wooden surfaces in the interior and exterior.

Properties: It protects the wood and penetrates deep into the pores of the wood. It is resistant to the influence of moisture.

Method of application:

It is applied in one layer with a brush, on a sanded and clean wooden base.

It does not dilute. Drying between layers is 16-24 hours, after which sanding and removal of sanding residues is performed, which ensures the application of the next coating.

Tools are washed with an oil thinner.

Technical data:

Delivery viscosity (F/4, 20°C): 13 ± 1 s

Content of non-volatile substances: 30 ± 2 %

Specific weight (20°C) : 0.84 ± 0.01 kg/lit.

Drying time: (at 20°C, 65% humidity)

- on dust: 60 min.
- on touch: 4h
- full 24h

Consumption:

1 liter is enough for 8-10 m², in one layer, depending on the type of wood.

Delivery form:

Delivered in PET packaging of 1 liter. and tin packaging 5 lit. And 20 lit.

Storage:

24 months in the original packaging, at a temperature of up to 30°C.

Precautions

The application of safety measures at work and fire protection is mandatory. Follow the manufacturer's instructions and safety data sheets.

The technical data are given in order to optimally use the product.

For all necessary information, contact the manufacturer