



TEHNICAL DATA BETONAL

Basic characteristics

Coat based on acryl binder, pigments , organic solvent's and helping aids.

Usage:

Used for protection and decoration of floors , balcony, garage, basement and all other rooms that have mild scuffing .Coat protects floors from concrete , natural stone , unfinished ceramic plates, wood, plywood etc

Properties

Easy and simple application , great coverage ,and make surface with silky shine

Resistant on atmosphere influence and mild scuffing Can be applied in temperature interval from 0 till 40

Application manner

Applied in 2-3 layers on dry surface , cleaned from dust and fat. First layer is brought by brush and diluted by adding 10 % of BETONAL solvent. Other layers should be brought by brush , roller or spraying with dilution of 5 % . Every next layer should be brought on 6-8 after first one.

Consumption g/m2 :

1 liter is enough for 5-8 m2

Shape of delivery

Its delivered in different shades , according to shade map

Storage

36 months in original package by temperature till 30 C

Flammability

I B group (JUS Z.CO.007)

Produced by: „CHIARA“ d.o.o. Brčko Distrikt BiH, Bescarinska zona bb,

Tel: 049 240400, fax: 049 240401 . e:mail : info@chiara.ba,

web site : www.chiara.ba

Technical data are given in order to achieve optimal usage of product. For all informations you can contact manufacturer